



YoLong^{Industrial}



YOLONG HOPSTORM_FOR DRY HOPPING

YoLong **HopStorm** designed for dry hopping, inner central assembly with one filter, two or three reverse tangential side beer inlet make hops be even and full mixing, assembly with safety valve or CO2 pressure relief valve to hold pressure and discharge the oxygen out of **HopStorm**.



SPECIAL DESIGN FOR DRY HOPPING

- High efficiency for dry hopping
- Simple operation, optimize fermentation period
- Customized available according beer type and hops adding
- High transfer rate of hops aroma and oil
- Electric heating tube, Dual function of CIP for small tank--Optional
- Mounted W VFD Pump--Optional



YOLONG HOPSTORM_ FOR DRY HOPPING



- Available capacity of 3kg to 200kg Hops
- Top Pressure Manway
- Safe valve (0-0.4MPa)
- Pressure gauge (0-0.6MPa)
- Assembly Sanitary Spray Balls for Cleaning
- Side sight glass
- Pipe sight glass
- Bottom hop Outlet
- SKID Frame with Four Casters
- Candle Filter
- Butterfly Valves
- Mounted W VFD Pump--Optional



SPECIFICATIONS OF HOPSTORM

Hop Pellets Type 45 or 90(kg)	3	5	10	15	20	25	30	40	50	80	100	150	200
Work Volume (L)	30	40	75	110	150	190	225	300	375	550	750	1150	1500
Total Volume (L)	38	60	95	130	210	250	285	360	435	620	820	1220	1580
Design Pressure (bar)	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
Height (mm)	1620		2190			2400			2670		3525	3850	4010
OD (mm)	480		750			1405			1520		1690	1795	1850
Hops Adding Height (mm)	1280		1595			1780			2060		2910	3230	3385
Filter Length (mm)	600		1200			1450			1750		2430	2790	2950
Head Space (mm)	/		645			840			1140		1820	2170	2325
Work Platform (mm)	/		395			580			860		1710	2030	2185
Price(FOB) USD	4640	5150	5750	5860	6590	6640	6890	7500	7630	8010	12960	14900	15700