


Technical parameter		
	Inner shell	Outer shell
Material	SUS304	SUS304
Thickness	3mm	2mm
Heating area m <sup>2</sup>	2.6	
Insulation	Mineral wool	
Total volume	14.2 bbl	
Working volume	10 bbl	

Specification			
Symbol	Spec	Connecting Style	Usage
M	ø450	Welding	Glass manway
N <sub>1</sub>	1.5"	Tri-clamp	Inlet
N <sub>2.1</sub> -N <sub>2.2</sub>	1.5"	Tri-clamp	outlet
N <sub>3.1</sub> -N <sub>3.2</sub>	0.75"	NPT	Condensation outlet
N <sub>4.1</sub> -N <sub>4.2</sub>	0.75"	NPT	Steam inlet
N <sub>6</sub>	1.5"-1"	Tri-clamp	Tangential inlet
N <sub>7</sub>	1.5"	Tri-clamp	Drain
N <sub>11</sub>	1.5"	Tri-clamp	Spray ball
N <sub>12</sub>	6"	Tri-clamp	Stacker
N <sub>13</sub>	4"	Tri-clamp	Hops adding hole
T	1.5"	Tri-clamp	Thermowell
N <sub>14</sub>	1.5"	Tri-clamp	Condensation outlet
N <sub>15</sub>	4"	Bevel seat	Tank light
N <sub>16</sub>	1"	Tri-clamp	Cold water inlet
L <sub>1-2</sub>	1.5"	Tri-clamp	Level

Mark	Revision Text	Places	Partitioning	Rev. No.	Signature	Date	Mark	Revision Text	Places	Partitioning	Rev. No.	Signature	Date
1				1	all	V1.0	Winson chang	2019.03.28					

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <YOLONG INDUSTRIAL CO., LTD.>. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <YOLONG INDUSTRIAL CO., LTD.> IS PROHIBITED.



客户图标	YI-04-0327A19
10bbl KW-D1400	1:16
图纸编号	10bbl KW-D1400
第 页 / 共 页	